



7.62mm (.300") Pitch MX150L™ Sealed Wire-to-Wire Plugs, Receptacles and Terminals 8, 10, 12 AWG

- 19433** Plugs
- 19432** Receptacles
- 19431** Male Terminals
- 19434** Female Terminals

Additional pitch and wire gauge options enhance Molex's high-performance MX150L connector system, which is designed for challenging, rugged and harsh applications

The MX150L 8, 10 and 12 AWG additions are designed to meet the need for a rugged, environmentally sealed connector system supporting high-power applications and long-voltage runs to eliminate voltage drops. The new pitch and wire gauge options add to the existing product family of 14 – 22 AWG with a 5.84mm (.230") pitch. The 7.62mm (.300") pitch supports up to 40 amps per circuit.

This innovative mat-sealed connector family is based upon a 2.50mm (.098") blade-type terminal system, available in a pre-Tin finish. This design eliminates the need to purchase, handle and crimp individual wire seals, which lowers applied cost. The mat-seal design is a single silicone-based seal with individual wire openings and a seal cap to protect, securely retain, and provide strain relief to the seal. The cost-effective connector design features all-in-one plug and receptacle housings with pre-assembled mat-wire and interfacial connector seals. Integral terminal position assurance (TPA) and connector position assurance (CPA) components eliminate time-consuming and costly assembly operations. Populating the housings consists

of crimp-and-poke technology. Simply crimp the appropriate terminal, insert the crimped terminal lead, and seat the TPA to it's lock position. No additional components are required.

Tooling solutions include FineAdjust™ crimp press applicators for high-volume production, as well as hand tools for low-volume production and field repairs.



Features and Benefits

- Pre-assembled connector housings and TPA components shipped in one-piece units for applied labor and cost savings
- Simple crimp, poke and plug application eliminates need to crimp individual wire seals
- Integral terminal position assurance (TPA) assures that crimped terminal leads are properly locked into connector (TPA will not seat into final lock position and connector system will not latch if terminal is not locked properly into position)
- Integral, two-way mat seal on the mating connector designed and tested to IEC IP 67 exceeds "waterproof" demands as a true sealed connector system tested under submersed conditions in various fluids
- Two independent terminals (10 to 12 AWG and 8 AWG) allow customers to support 30amp applications with 10 to 12 AWG terminals and 40amp applications with 8 AWG terminals
- Audible and tactile feedback clicks on insertion, extraction and mating facilitates reliable mating and terminal loading and removal
- 7.62mm (.300") pitch housing design with 2 styles of terminals for wire styles from 10 to 12 AWG as well 8 AWG allows flexibility in selecting from a wide range of wire styles and insulation thicknesses, (nominal O.D. ranges .155 to .237") to support numerous applications

SPECIFICATIONS

Reference Information

Packaging:
Housings — Bulk
Terminals — Reel and loose piece
UL File No.: E152602
Designed In: Inches

Electrical

Voltage: 600V
Current: 10 to 12 AWG — 30.0A
8 AWG — 40.0A
Dielectric Withstanding Voltage: 2200V AC min.
Insulation Resistance: 1000 Megohms

Mechanical

Contact Insertion Force: 4.4N (1 lbf) max.
Sealing: IEC 529 — IP67 standard
Durability: 25 cycles

Physical

Housing: Glass-filled PBT, Black
Contact: Copper (Cu) Alloy
Plating: Tin (Sn)
Operating Temperature: -40 to +125°C
Flammability: UL 94V-0

APPLICATIONS

- Agriculture equipment
- Construction equipment
- Recreational vehicles
- Marine equipment




7.62mm (.300")
PitchMX150L™ Sealed
Wire-to-Wire Plugs,
Receptacles and Terminals
8, 10, 12 AWG


19433 Plugs
19432 Receptacles
19431 Male Terminals
19434 Female Terminals

ORDERING INFORMATION


Female Terminals

 10-12 AWG 8 AWG	AWG	Insulation Diameter mm (in)	Order No.		Dimensions mm (in)			
			Loose	Strip	A	B	C	D
	10-12	3.94-4.45 (.155-.175)	19434-0003	19434-0001	6.35 (.250)	6.00 (.236)	5.00 (.197)	5.60 (.220)
	8	6.02 (.237)	19434-0004	19434-0002	N/A	N/A	6.10 (.240)	7.0 (.276)


Male Terminals

 10-12 AWG 8 AWG	AWG	Insulation Diameter mm (in)	Order No.		Dimensions mm (in)			
			Loose	Strip	A	B	C	D
	10-12	3.94-4.45 (.155-.175)	19431-0016	19431-0001	6.35 (.250)	6.00 (.236)	5.00 (.197)	5.60 (.220)
	8	6.02 (.237)	19431-0017	19431-0015	N/A	N/A	6.10 (.240)	7.00 (.276)


Single-Row Receptacle

	Order No.	Circuits	Wire Range (AWG)	Mat Seal Color
	19432-0013	2	10-12	Yellow
	19432-0014		8	Red


Single-Row Plug

	Order No.	Circuits	Wire Range (AWG)	Mat Seal Color
	19433-0013	2	10-12	Yellow
	19433-0014		8	Red

Dual-Row Receptacle - 8, 10, 12 AWG

	Order No.	Circuits	Wire Range (AWG)	Mat Seal Color
	19432-0001	4	10-12	Yellow
	19432-0002		8	Red

Dual-Row Plug - 8, 10, 12 AWG

	Order No.	Circuits	Wire Range (AWG)	Mat Seal Color
	19433-0001	4	10-12	Yellow
	19433-0002		8	Red

Americas Headquarters
 Lisle, Illinois 60532 U.S.A.
 1-800-78MOLEX
 amerinfo@molex.com

Far East North Headquarters
 Yamato, Kanagawa, Japan
 81-462-65-2324
 feninfo@molex.com

Far East South Headquarters
 Jurong, Singapore
 65-6-268-6868
 fesinfo@molex.com

European Headquarters
 Munich, Germany
 49-89-413092-0
 eurinfo@molex.com

Corporate Headquarters
 2222 Wellington Ct.
 Lisle, IL 60532 U.S.A.
 630-969-4550
 Fax: 630-969-1352

Visit our website at www.molex.com/mx150Lsealedwtw.html